

NEC 46" ULTRA NARROW BEZEL LCD X462UN



NEC 46" ULTRA NARROW LCD : WALL CONFIGURATION



NEC 46" ULTRA NARROW LCD : BESPOKE FRAME DETAIL

DISPLAY PANEL	
Viewable Size (Diagonal)	46"
Native Resolution	1366 x 768
Pixel Pitch	0.746mm
Brightness (typical)	500 cd/m ² (700 cd/m ² max)
Contrast Ratio (typical)	3000:1
Active Screen Area (W X H)	1018.4 x 572.5mm

CONNECTIVITY	
Input Terminals	
Digital	DisplayPort, HDMI, DVI-D
Analog	Analog D-sub, 5BNC (RGBHV), BNC Composite, RCA Composite (Y, Cb/Pb, Cr/Pr), S-Video
Audio	RCA Audio x 2, DisplayPort Audio, HDMI Audio
External Control	RS-232, RJ-45 LAN, DDC/CI, IR Remote
Output Terminals	
Analog	5 BNC (RGBHV), BNC Component
Audio	Stereo Mini-Jack, RCA Audio
External Control	RS-232, IR Remote

POWER	
Power Requirements	3.6A @ 100-120V AC; 1.45A @ 220-240V AC
Power Consumption (typical)	200W (330W max.)
Power Consumption - ECO Standby	<2W

PHYSICAL SPECIFICATIONS	
Bezel Width (L/R, T/B)	4.5mm/2.7mm, 4.5mm/2.7mm
Dimensions (without stand; WxHxD)	1025.7 x 579.8 x 128.1mm
Net Weight (without stand)	29.3kg
VESA Hole Configuration	300 x 300mm (4 hole)

ENVIRONMENTAL CONDITIONS	
Operating Temperature	5° - 40°C / 41° - 104°F
Operating Humidity	20 - 80%

